

Specifications

DTH

RF performance

	C-Band 180 cm Series	Ku-Band 180 cm Series
F/D	0.375	0.375
Operating frequency	3.40 – 4.20 GHz	10.70 – 12.75 GHz
Gain (± 0.3 dBi)	37.50 dBi @ 4.20 GHz	46.35 dBi @ 12.75 GHz
3 dB beamwidth	2.1° @ 4.2 GHz	1.0° @ 12.75 GHz
Antenna Cross-Polarization	> 30 dB (on axis)	> 30 dB (on axis)
VSWR	1.3 : 1 Max.	1.3 : 1 Max.

Mechanical performance

Material	Steel	Steel
Antenna Optics	Six-Panel steel reflector prime focus	Six-Panel steel reflector prime focus
Mount Type	Elevation over azimuth	Elevation over azimuth
Elevation Adjustment Range	0° - 90° continuous fine adjustment	0° - 90° continuous fine adjustment
Azimuth Adjustment Range	360° Continuous	360° Continuous
Mast Pipe Size	76mm - 89mm OD	76mm - 89mm OD
Wind Loading (Operational) (Survival)	80 km/h 180 km/h	80 km/h 180 km/h
Temperature (Operational)	-40°C to 60°C	-40°C to 60°C
Rain (Operational)	10 mm/h	10 mm/h
Atmospheric Conditions	Salt, Pollutants and Contaminants as encountered in coastal and industrial areas: 720 hours ASTM B117 salt spray	Salt, Pollutants and Contaminants as encountered in coastal and industrial areas: 720 hours ASTM B117 salt spray
Humidity	0 to 100% with condensation	0 to 100% with condensation



www.azureshine.com.tw | Email: azure.shine@azureshine.com.tw

Azure Shine Technology Co., Ltd.

No. 1000, Guangfu Rd., Bade Dist., Taoyuan City, 33455, Taiwan, R.O.C.

Tel: +886-3-3611393 | Fax: +886-3-3615877