

Specifications

DTH

RF performance

	Ku-Band 35 cm Series
F/D	0.5
Operating frequency	10.70 – 12.75 GHz
Gain (± 0.3 dBi)	32.50 dBi @ 12.75 GHz
3 dB beamwidth	4.50° @ 12.75 GHz
Antenna Cross-Polarization	> 30 dB (on axis)
VSWR	1.3 : 1 Max.



Mechanical performance

Material	Steel
Antenna Optics	One-piece offset feed prime focus
Mount Type	Elevation over azimuth
Elevation Adjustment Range	0° - 90° continuous fine adjustment (On glass) 10° - 90° continuous fine adjustment (On table)
Azimuth Adjustment Range	360° Continuous
Mast Pipe Size	Include the cupule kit
Wind Loading (Operational)	80 km/h
Temperature (Operational)	-40°C to 60°C
Rain (Operational)	10 mm/h
Atmospheric Conditions	Salt, Pollutants and Contaminants as encountered in coastal and industrial areas: 720 hours ASTM B117 salt spray
Humidity	0 to 100% with condensation



www.azureshine.com.tw | Email: azure.shine@azureshine.com.tw

Azure Shine International Inc.

No. 1000, Guangfu Rd., Bade Dist., Taoyuan City, 33455, Taiwan, R.O.C.

Tel: +886-3-3611393 | Fax: +886-3-3615877